

Incandescent Work Lights

Corded Incandescent Work Lights



BL-15

**12
volt**



PRO Δ LITE™ Speciality Incandescent Lighting

Part	Description	Rep. Bulbs	Cord Length	Wire Gauge/ Cord Type	Max Rating
BL-15	12V automotive work light with battery clamps. Special bulb included. On-off switch in handle. Swivel hook.	60W, 12V included	15 ft.	18/2 SPT1	12V DC



**TL-25P
TL-25PN
TL-6P**



**TL-50GM
TL-25GM‡**



MCL6P



PRO Δ LITE™ Incandescent Work Lights

Part	Description	Outlet	Bulb	Cord Length	Wire Gauge/ Cord Type	Max Rating
TL-6P	On-off switch built into handle plastic swing-open bulb guard with swivel hook.	N/A	75 watt	6 ft.	18/2 SJT	75W 125V
TL-25P	On-off switch, plastic swing open guard swivel hook.	N/A	75 watt	25 ft.	18/2 SJT	75W 125V
TL-25PN	Same as TL-25P except no switch meets NEC 511 (1) for use in commercial garages. Cord and lamp head must be supported so that they cannot reach within 18" of the floor.	N/A	75 watt	25 ft.	18/2 SJT	75W 125V
TL-25GM‡	On-off switch built into handle. Grounded metal swing-open bulb guard with hanging hook.	Built-in	100 watt	25 ft.	16/3 SJT	1625W 13A 125V
TL-50GM	On-off switch, grounded swing open metal guard, fixed hook.	Built-in	100 watt	50 ft.	16/3 SJT	1625W 13A 125V
MCL6P	4 in 1 incandescent work light, stick it, clamp it, hang it and stand it. With aluminum reflector shade.	No	60 watt	6 ft.	18/2 SJTW	60W .480A 125V

Bulb not included—maximum bulb rating shown ‡Display tray pack packaging

Corded Incandescent Work Lights



100W TL-25GM-CB



**100W TLP-25GM-CB
TLP-50GM-CB**



PRO _Δ LITE™ Professional Incandescent Work Lights						
Part	Description	Outlet	Bulb	Cord Length	Wire Gauge/ Cord Type	Max Rating
TL-25GM-CB	On-off switch, grounded swing open metal guard, fixed hook.	Built-in with circuit breaker	100 watt	25 ft.	16/3 SJT	1625W 13A 125V
TLP-25GM-CB	On-off switch, grounded metal guard 360° rotary hook, all weather cord.	Built-in with circuit breaker	100 watt	25 ft.	16/3 SJTOW	1625W 13A 125V
TLP-50GM-CB	On-off switch, grounded metal guard 360° rotary hook, all weather cord.	Built-in with circuit breaker	100 watt	50 ft.	16/3 SJTOW	1625W 13A 125V

Bulb not included—maximum bulb rating shown



**100W HTL-25M-CB
HTL-50M-CB**



PRO _Δ LITE™ Professional Incandescent Work Lights						
Part	Description	Outlet	Bulb	Cord Length	Wire Gauge/ Cord Type	Max Rating
HTL-25M-CB	Grounded metal reflector with heavy duty metal reflector/bulb guard, on-off switch.	Built-in with circuit breaker	100 watt	25 ft.	14/3 SJTW	1875W 15A 125V
HTL-50M-CB	Grounded metal reflector with heavy duty metal reflector/bulb guard, on-off switch.	Built-in with circuit breaker	100 watt	50 ft.	14/3 SJTW	1875W 15A 125V

Bulb not included—maximum bulb rating shown

Corded Incandescent Temporary Lighting



**5 x 150W TLS-50
TLS-100**



**10 x 150W TLS-100J2
TLS-50J3**

5 x 150W TLS-100J3



**75W TPL-25
TPL-50**



PRO _Δ LITE™ Professional Incandescent Work Lights					
Part	Description	Bulb	Cord Length	Wire Gauge/ Cord Type	Max Rating
TLS-50	Molded-on weather resistant lamp sockets with durable plastic bulb guards spaced on 10 ft. centres. Linkable.	5 x 150 watt	50 ft.	12/3 STW	2500W 15A 125V
TLS-100	Molded-on weather resistant lamp sockets with durable plastic bulb guards spaced on 10 ft. centres. Linkable.	10 x 150 watt	100 ft.	12/3 STW	2500W 15A 125V
TLS-100J2**	Molded-on weather resistant lamp sockets with plastic bulb guards spaced on 10 ft. centres. Non-linkable.	10 x 150 watt	100 ft.	14/2 SJTW	1875W 15A 125V
TLS-50J3**	Molded-on weather resistant lamp sockets with metal cage bulb guards spaced on 10 ft. centres. Linkable.	5 x 150 watt	50 ft.	12/3 SJTW	2500W 15A 125V
TLS-100J3**	Molded-on weather resistant lamp sockets with metal cage bulb guards spaced on 10 ft. centres. Linkable.	10 x 150 watt	100 ft.	12/3 SJTW	2500W 15A 125V
TPL-25	Single temporary pendant light with solid rubber handle molded to cord. Clear vented polycarbonate guard—rainproof when used as a pendant.	75 watt	25 ft.	16/2 S00W	75W 15A 125V
TPL-50	Single temporary pendant light with solid rubber handle molded to cord. Clear vented polycarbonate guard—rainproof when used as a pendant.	75 watt	50 ft.	16/2 S00W	75W 15A 125V

Bulb not included—maximum bulb rating shown **UL specified only, not CUL

Incandescent Work Lights on Reels

PRO REEL™



5000A-30G



5000-30G-CB

**PRO REEL™
PROFESSIONAL**



**5000A-30G-CB
5000A-30G-CBP**



5000-35G-SSP*



**PRO REEL™
INDUSTRIAL**



8050M-W

PRO REEL™ Incandescent Retractable Cord Reel Work Lights

Part	Description	Outlet	Bulb	Cord Length	Wire Gauge/ Cord Type	Max Rating
5000A-30G	Powder coated metal reel housing, grounded metal guard, on-off switch.	Built-in	75 watt	30 ft.	16/3 SJT	1250W 10A 125V
5000-50G-CB	Powder coated metal reel housing, grounded metal guard, on-off switch.	Built-in with circuit breaker	75 watt	50 ft.	18/3 SJT	875W 7A 125V
5000A-30G-CB	Powder coated metal reel housing, grounded metal guard, on-off switch.	Built-in with circuit breaker	75 watt	30 ft.	16/3 SJT	1250W 10A 125V
5000A-30G-CBP	Same as 5000A-30G-CB with powder coated metal reel, metal bulb guard with swivel hook and 30 ft. all-weather cord.	Built-in with circuit breaker	75 watt	30 ft.	16/3 SJTOW	1250W 10A 125V
5000-35G-SSP	Powder coated steel reel with auto switching feature, nylon guard.±	N/A	75 watt	35 ft.	18/3 SJT	75W 125V
8050M-W	Industrial grade reel housing. Quick release mounting bracket. Convenient carrying handle. 360° reflector guard with rotary hook.	Built-in with circuit breaker	100 watt	50 ft.	14/3 SJTW	1625W 13A 125V

*Bulb not included - maximum bulb rating shown

± For safety code compliance the reel must be mounted a minimum of 12' above the floor and the cord and lamp head must be supported so they cannot reach 8" above the floor



920DT



PRO REEL™ DURATRAC Retractable Cord Reels

Part	Description	Outlet	Bulb	Cord Length	Wire Gauge/ Cord Type	Max Rating
920DT	Retractable plastic reel housing, resettable circuit breaker, grounded metal guard, side outlet and hook.	1 x built-in circuit breaker	100 watt	20 ft.	18/3 SVT	875W 7A 125V