



Work Lights & Cord Reels

Canada
2024



Where
INNOVATION
comes to **LIGHT**



merithian.com

Glossary of Wire and Terminology

Abbreviations

S = Service

J = Junior

O = Oil Resistant

T = Thermoplastic/Vinyl

W = Weather Resistant

P = Parallel

SJT Junior hard service thermoplastic insulated conductors with overall thermoplastic jacket.

SJTOW Hard service cord. Thermoplastic constructed jacket. Oil and weather resistant for outdoor use.

SJTW Hard service cord. Thermoplastic constructed jacket. 300 volt, weather resistant for outdoor use.

SPT-1 Thermoplastic constructed cord, parallel jacketed, 300 volt. 2 or 3 conductor, 18 gauge.

SPT-2 Same as SPY-1 except heavier construction. 18-16 gauge.

STW Hard service, indoor/outdoor water resistant outer jacket.

SVT Vacuum cleaner service cord. All plastic construction, 2 or 3 conductor.

AWG American Wire Gauge. A relative system for the designation of diameter.

Alternating Current (AC) or line voltage - U.S. household standard current is 110/120 volts, 60 cycle.

AMP Load Total amount of amperage flowing through a conductor (wire) when it is loaded.

Circuit The path that electricity flows through a conductor.

Compound Insulation or jacketing material of two or more ingredients.

Conductor Material (wire) that is capable of transporting and electrical charge easily. Cords can be two or three conductor.

Cord An insulated wire (conductor) for conveying current.

CRI Unit of measurement indicating Color Rendering Index. Higher units provide more true color to objects in comparison to appearance in natural sunlight.

CSA Canadian Standards Association, a non-profit, independent organization that operates a listing service for electrical and electronic materials and equipment. The Canadian counterpart of the Underwriters Laboratories.

Current The flow of electricity through a conductor measured in amperes.

Direct Current (DC) An electrical current that flows in one direction. Batteries are an example of DC current production.

ETL An independent, non-profit organization that operates a listing service for electrical/electronic materials /equipment and uses UL standards.

Gauge Term used to denote physical size of wire.

Ground Electrical term referring to connecting to the earth or large conducting body to serve as earth.

Insulation Non-conductive material that surrounds or separates two conductive materials (wire).

KELVIN Unit of measurement indicating Color Temperature. Below 2700K is Warm White, 4500K is Cool White and 7000K is Daylight.

LED Light emitting diode

- **5 MM** Round dome shaped lens emits light with a 10° - 20° beam out.

- **SMD** Surface Mounted Diode emitting brighter, wide beam pattern.

- **COB** Chips On Board has a series of diode chips mounted directly onto a circuit board. Wide beam pattern especially useful in compact mounting spaces.

LUMEN Unit of measurement for LED Light Output. Higher lumens = brighter light.

NEMA National Electric Manufacturers.

OSHA Occupational Safety and Health Act. Specifically the Williams-Steiger law passed in 1970 covering all factors relating to safety in places of employment.

Polarity Condition by which the direction of current flow can be determined in an electrical circuit.

Polarized Plug A plug constructed to allow insertion into a receptacle only one way because one blade is wider than the other.

PVC Polyvinyl Chloride. Compound used in thermoplastic cords.

Rated Voltage Maximum voltage at which an electrical component can be operated for extended periods without causing a safety hazard or undue degradation.

Resistance A substance that impedes the flow of current resulting in loss of power, such as heat.

Sheath Outer jacket or covering of multi-conductor cable.

Thermoplastic Plastic material that softens when heated and firms when cooled. Examples are Polyvinyl Chloride and Polyethylene.

UL Underwriters Laboratories, an independent, non-profit organization that operates a listing service for electrical/ electronic materials / equipment.

Volt Unit to measure electromotive force.

Watt Unit of electrical power defined as one amp of current driven by one volt of electromotive force.

All Alert products are individually tested and inspected for defects in material and workmanship before leaving the factory. Should your Alert product fail within the warranty period due to faulty workmanship or material, simply return it to the original place of purchase for a replacement.

Our Return Policy is limited to the replacement of the original purchase. No other liability, responsibility or warranty is expressed or implied including any regarding merchantability or fitness for a particular purpose.



Contents

LED Work Lights, Cordless Rechargeable	4
LED Work Lights, Coded	5
LED Flood Lights & Stands	6
LED Retractable Work Light Reels	7
Retractable Reels, Various	8
Retractable Extension Cord Reels	8
Weather Proof NEMA 3R Reels	9
Incandescent Work Lights	10
Fluorescent Work Lights	10
Incandescent Clamp Lamps	11
Retractable Incandescent Work Reels	11
Retractable Data Reels	11



LED Work Lights, Cordless Rechargeable

KWR12



NEW

KWR700T



KCR5



KCR10



Catalog No.
Description/UPC

Pack

Weight

Battery
Type

KWR12

12 SMD LED 360 LUMEN RECHARGEABLE RAINPROOF TASK LIGHT. IP65 RAINPROOF RATED, ROTATING HANG HOOK, RUBBERIZED HANDLE, 3.7V LI-ION BATTERY, SEALED PUSH SWITCH, CHARGE STATUS INDICATOR LIGHT AND MAGNETIC BASE.

UPC 0-40082-83042-3



4

3.6 lbs

Rechargeable Lithium Ion

KWR700T

70-700 LUMEN COB LED TILT LIGHT. FULLY FOLDABLE LIGHT BAR - ROTATES 180 DEGREES. 3.7V 2600 MAH LI-ION BATTERY. DIMMER SWITCH CONTROLS 70-700 LUMENS. 120 LUMEN LED FLASH LIGHT. IP54 RAINPROOF. BATTERY LEVEL/CHARGE STATUS INDICATOR LIGHTS. MAGNET & HOOK FOR HANDS-FREE USE. RUBBERIZED HANDLE. INCLUDES USB-C CABLE

UPC 0-40082-00000-0



6

7.4lbs

Rechargeable Lithium Ion

KCR5

5 WATT COB LED 400 LUMEN RECHARGEABLE TASK LIGHT. 3000mAh LITHIUM ION BATTERY, FOLDING SWIVEL HOOK, OVERMOLDED COMFORT RUBBER HANDLE AND MICRO USB CHARGER.

UPC 0-40082-01288-1



4

4.4 lbs

Rechargeable Lithium Ion

KCR10

800 LUMEN RECHARGEABLE COB WORKLIGHT. 3.7V, 4400mAh LI-ION BATTERY, USB C CHARGE PORT, PUSH BUTTON ON/OFF SWITCH, INTEGRATED MAGNET, FOLDING HOOK ROTATES 360°, WIDE STAND BASE W/ MAGNET. MAX 6 HOUR RUN TIME ON LOW SETTING.

UPC 0-40082-05934-3

4

8.2 lbs

Rechargeable Lithium Ion

LHR5200

RECHARGEABLE COB LED AUTO HOOD LIGHT. TWO DETACHABLE WORK/FLOOD LIGHTS WITH DUAL BRIGHTNESS LEVELS: 1200 LUMENS ON HIGH AND 600 LUMENS ON LOW, CHARGE STATUS INDICATOR LIGHTS, MAGNETIC BASE TILTS AND ROTATES, RAIN TIGHT. CAN ALSO BE USED AS A USB POWER BANK TO CHARGE YOUR DEVICE. BRACKET EXTENDS UP TO 78" AND CAN STAND ON FLAT SURFACES. UP TO 7 HOUR RUN TIME. USB-C CORD AND CHARGER PLUG INCLUDED.

UPC 0-40082-31095-4



4

28.45 lbs

Rechargeable Lithium Ion

LHR5200



LED Work Lights, Corded

RTL30SM



RTL30SM

30 SMD LED 350 LUMEN TROUBLE LIGHT REPLACEMENT MODULE. HEAD ROTATES 320°, FOLDING TOP HANG SWIVEL HOOK, PROTECTIVE BUMPERS.

UPC 0-40082-01289-8



5*

4.8 lbs

N/A

N/A

N/A

KWC625

8 WATT COB LED 500 LUMEN CORDED TASK LIGHT. MAGNET OR HOOK MOUNTABLE. WATERPROOF, IP65. IMPACT RATING: IK07. 25 FT, SJTW 18/2 CORD

UPC 0-40082-05940-4



6

12.6 lbs

25 ft

18/2

SJTW

KCL815

8 WATT COB LED 975 LUMEN TASK LIGHT. PUSH BUTTON ON/OFF SWITCH, BUILT IN NEODYMIUM MAGNET, FOLDING SWIVEL HOOK AND OVERMOLDED COMFORT RUBBER HANDLE.

UPC 0-40082-43056-2



4*

6.6 lbs

15 ft

18/2

SJT

KTM3315G

1300 LUMEN COB LED TASK LIGHT. GROUNDED OUTLET AND PUSH BUTTON ON/OFF SWITCH, IN HANDLE, INTEGRATED MAGNET, SWIVEL HOOK, POWER "ON" INDICATOR LIGHT, OVER MOLDED RUBBER HANDLE, 15' 16/3 SJT CORD.

UPC 0-40082-43078-4



4*

12.25 lbs

15 ft

16/3

SJTOW

NEW

KWC625



KCL815



KTM3315G



LED Flood Lights



LZR10C



LF84S




LF140S



LF168ST



LF240ST

Catalog No. Description/UPC	Pack	Weight	Cord Length	Wire Gauge	Wire Type	Maximum Rating
LZR10C RECHARGEABLE COB FLOOD LIGHT. DUAL OUTPUT BRIGHTNESS 1200 AND 600 LUMENS. PUSH BUTTON ON/OFF SWITCH, USB-C CHARGER, CHARGE STATUS INDICATOR LIGHTS, MAGNETIC BASE TILTS AND ROTATES, RAIN TIGHT. CAN ALSO BE USED AS A USB POWER BANK TO CHARGE YOUR DEVICE.						
UPC 0-40082-31096-1		4	4.5 lbs	RECHARGEABLE LITHIUM ION BATTERY		
LF84S 84 SMD LED 5000 LUMEN PORTABLE FLOODLIGHT. 50,000 HOUR LIFE. IP54 RAINPROOF RATED. RUGGED CAST ALUMINUM BODY, POWDER COATED FINISH. 6 FT 18/3 SJTW CORD - PUSH BUTTON ON/OFF SWITCH.						
UPC 0-40082-98187-3		4	15.5 lbs	6 ft.	18/3 SJTW	52W 0.45A 120V
LF140S 140 SMD LED 10,000 LUMEN PORTABLE FLOODLIGHT. 50,000 HOUR LIFE. IP54 RAINPROOF RATED. RUGGED CAST ALUMINUM BODY, POWDER COATED FINISH. 6 FT 18/3 SJTW CORD - WEATHER RESISTANT SWITCH BUTTON ON/OFF						
UPC 0-40082-98188-0		4	18.7 lbs	6 ft.	18/3 SJTW	64W 0.55A 120V
LF168ST TWIN 84 SMD LED FLOODLIGHTS WITH 10,000 LUMEN OUTPUT AND 56" TRIPOD. 50,000 HOUR LIFE. IP54 RAINPROOF RATED. RUGGED CAST ALUMINUM BODY, POWDER COATED FINISH. 6 FT 18/3 SJTW CORD - PUSH BUTTON ON/OFF SWITCH.						
UPC 0-40082-98189-7		2	25.8 lbs	6 ft.	18/3 SJTW	103W 0.86A 120V
LF240ST TWIN 120 SMD LED FLOODLIGHTS WITH 14,000 LUMEN OUTPUT AND 56" TRIPOD. 50,000 HOUR LIFE. IP54 RAINPROOF RATED. RUGGED CAST ALUMINUM BODY, POWDER COATED FINISH. 6 FT 18/3 SJTW CORD - PUSH BUTTON ON/OFF SWITCH.						
UPC 0-40082-98190-3		2	28.64 lbs	6 ft.	18/3 SJTW	130W 1.1A 120V

LED Retractable Work Light Reels



920LSM

Catalog No. Description/UPC	Cord Type Gauge/ Length	Maximum Rating	Master Pack	Master Cubic Feet	Master Weight
--------------------------------	-------------------------------	-------------------	----------------	----------------------	------------------

920LSM

18 SMD LED 150 LUMEN RETRACTABLE CORD REEL TASK LIGHT, 20FT 18/2 SVT CORD WITH HIGH-IMPACT PLASTIC REEL HOUSING AND ON/OFF SWITCH BUILT INTO HANDLE, SWIVEL HANGING HOOK, TOP AND BOTTOM PROTECTIVE BUMPERS.

UPC 0-40082-01284-3



SVT 18/2
20 ft 3.5 WATT
0.05A 120V

4

.94 CU ft

17.2 lbs

3230SMS

30 SMD LED 300 LUMEN RETRACTABLE CORD REEL TASK LIGHT. POWDER COATED STEEL REEL HOUSING, ON/OFF SWITCH IN HANDLE. DUAL FOLDING SWIVEL HOOKS, REMOVEABLE ROTATING MAGNET.

UPC 0-40082-01290-4



SJT 18/2
30 ft 5 WATT
.07A 120V

4

1.88 CU ft

31 lbs

5050CL8

8 WATT COB LED 975 LUMEN CORD REEL. RUGGED POWDER COATED STEEL REEL, POWER "ON" INDICATOR LIGHT, BUILT IN NEODYMIUM MAGNET, FOLDING SWIVEL HOOK AND OVERMOLDED COMFORT RUBBER HANDLE.

UPC 0-40082-43057-9



SJT 18/2
50 ft 8 WATT
.13A 120V

4

2.17 CU ft

38 lbs

5030AM

1300 LUMEN COB LED CORD REEL TASK LIGHT. GROUNDED OUTLET AND ON/OFF SWITCH IN HANDLE, INTEGRATED MAGNET, SWIVEL HOOK, POWER "ON" INDICATOR LIGHT, OVER MOLDED RUBBER HANDLE.

UPC 0-40082-43079-1



SJTOW 16/3 1440 WATT
30 ft 12A 120V

4

2.29 CU ft

39.8 lbs

8150MM

1300 LUMEN COB LED CORD REEL TASK LIGHT. GROUNDED OUTLET AND ON/OFF SWITCH IN HANDLE, INTEGRATED MAGNET, SWIVEL HOOK, POWER "ON" INDICATOR LIGHT, OVER MOLDED RUBBER HANDLE. INDUSTRIAL GRADE THERMOPLASTIC HOUSING, REMOVEABLE STEEL MOUNTING BRACKET, CONVENIENT CARRY HANDLE.

UPC 0-40082-43116-3



SJTOW 14/3 1625 WATT
50 ft 13A 125V

2

2.1 CU ft

30.4 lbs



3230SMS



5050CL8



5030AM



8150MM


Retractable Extension Cord Reels & Portable Multi-plug Cord Tenders



Catalog No. Description/UPC	Cord Type Gauge/ Length	Maximum Rating	Circuit Breaker	No. of Outlets	Master Pack	Master Cubic Ft	Master Weight
--------------------------------	-------------------------------	-------------------	--------------------	-------------------	----------------	--------------------	------------------


8140T-P

HEAVY-DUTY INDUSTRIAL GRADE REEL HOUSING, QUICK RELEASE STEEL MOUNTING BRACKET, CONVENIENT CARRYING HANDLE, TRI-TAP WITH 3 GROUNDED OUTLETS WITH POWER "ON" INDICATOR LIGHT & BUILT IN CIRCUIT BREAKER. 40 FT. SJTOW 12/3 CORD.

UPC 0-40082-43071-5	 SJTOW 12/3 40 ft	1875 WATT 15A 125V	YES	3	2	1.6 CU ft	31 lbs
---------------------	---	--------------------------	-----	---	---	-----------	--------


8150M-P

HEAVY-DUTY INDUSTRIAL GRADE REEL HOUSING, QUICK RELEASE STEEL MOUNTING BRACKET, CONVENIENT CARRYING HANDLE, TRI-TAP WITH 3 GROUNDED OUTLETS WITH POWER "ON" INDICATOR LIGHT & BUILT IN CIRCUIT BREAKER. 50 FT. SJTOW 14/3 CORD.

UPC 0-40082-43072-2	 SJTOW 14/3 50 ft	1625 WATT 13A 125V	YES	3	2	1.6 CU ft	25 lbs
---------------------	---	--------------------------	-----	---	---	-----------	--------


8675MFT

HEAVY-DUTY INDUSTRIAL GRADE REEL HOUSING, REMOVEABLE STEEL MOUNTING BRACKET, CONVENIENT CARRYING HANDLE, CIRCUIT BREAKER PROTECTED LIGHTED TRI-TAP WITH PUSH BUTTON LOCKING CENTER OUTLET.

UPC 0-40082-42067-8	 SJTOW 14/3 75 ft	1250 WATT 10A 125V	YES	3	2	1.9 CU ft	39.7lbs
---------------------	---	--------------------------	-----	---	---	-----------	---------


8665TFS

HEAVY-DUTY INDUSTRIAL GRADE REEL HOUSING, REMOVEABLE STEEL MOUNTING BRACKET, CONVENIENT CARRYING HANDLE, CIRCUIT BREAKER PROTECTED, LIGHTED CLEAR 5-15/20 SINGLE OUTLET.

UPC 0-40082-43059-3	 SJTOW 12/3 65 ft	1875 WATT 15A 125V	YES	1	2	1.9 CU ft	44 lbs
---------------------	---	--------------------------	-----	---	---	-----------	--------

8665TFQ

HEAVY-DUTY INDUSTRIAL GRADE REEL HOUSING, REMOVEABLE STEEL MOUNTING BRACKET, CONVENIENT CARRYING HANDLE, CIRCUIT BREAKER PROTECTED, FANNED QUAD 4 GROUNDED OUTLETS WITH LED POWER "ON" INDICATOR.

UPC 0-40082-43060-9	 SJTOW 12/3 65 ft	1875 WATT 15A 125V	YES	4	2	1.9 CU ft	46.3 lbs
---------------------	---	--------------------------	-----	---	---	-----------	----------

8645TFI

HEAVY-DUTY INDUSTRIAL GRADE REEL HOUSING, REMOVEABLE STEEL MOUNTING BRACKET, CONVENIENT CARRYING HANDLE, ILLUMINATED CLEAR 5-15/20 SINGLE OUTLET POWER BLOCK WITH LED POWER "ON" INDICATOR. 20A IN-LINE CIRCUIT BREAKER AND NEMA 5-20 MALE PLUG ON PIGTAIL.

UPC 0-40082-43061-6	 SJTOW 12/3 45 ft	2500 WATT 20A 125V	YES	1	2	1.9 CU ft	37.5 lbs
---------------------	---	--------------------------	-----	---	---	-----------	----------



Retractable Extension Cord Reels



Catalog No. Description/UPC	Cord Type Gauge/ Length	Maximum Rating	Circuit Breaker	No. of Outlets	Master Pack	Master Cubic Ft	Master Weight
--------------------------------	-------------------------------	-------------------	--------------------	-------------------	----------------	--------------------	------------------

5000A-30GF-CB

POWDER COATED STEEL RETRACTABLE CORD REEL HOUSING. POWER BLOCK WITH THREE GROUNDED OUTLETS AND BUILT IN RESETTABLE CIRCUIT BREAKER.

UPC 0-40082-00445-9	UL _{us} SJT 16/3 30 ft	1250 WATT 10A 125V	YES	3	4	1.5 CU ft	36.2 lbs
---------------------	------------------------------------	--------------------------	-----	---	---	-----------	-------------

5000M-30GF-CB

POWDER COATED STEEL RETRACTABLE CORD REEL HOUSING. POWER BLOCK WITH THREE GROUNDED OUTLETS, BUILT-IN RESETTABLE CIRCUIT BREAKER WITH HEAVY-DUTY 14/3 CORD.

UPC 0-40082-00492-3	UL _{us} SJTW 14/3 30 ft	1625 WATT 13A 125V	YES	3	4	1.6 CU ft	39.1 lbs
---------------------	-------------------------------------	--------------------------	-----	---	---	-----------	-------------

5020TF-4C

FOUR OUTLET HEAVY DUTY 20FT RETRACTABLE 12AWG EXTENSION CORD REEL WITH RUGGED POWDER COATED STEEL HOUSING, 15 AMP RESETTABLE CIRCUIT BREAKER PROTECTED 5-15P PLUG. FOUR 5-20R GROUNDED OUTLETS WITH POWER "ON" INDICATOR LIGHT. WALL OR CEILING MOUNT WITH INCLUDED HARDWARE.

UPC 0-40082-01254-6	UL _{us} SJTOW 12/3 20 ft	1875 WATT 15A 125V	YES	4	4	1.8 CU ft	41.4 lbs
---------------------	--------------------------------------	--------------------------	-----	---	---	-----------	-------------



Weather Proof NEMA 3R Reels



Catalog No. Description/UPC	Cord Type Gauge/Length	Maximum Rating	Circuit Breaker	No. of Outlets	Master Pack	Master Weight
--------------------------------	---------------------------	-------------------	--------------------	-------------------	----------------	------------------

5330M-SW

INDOOR/OUTDOOR RETRACTABLE EXTENSION CORD REEL WITH 30 FT, SJTOOW 14/3 WIRE. WATERTIGHT NEMA 5-15C CONNECTOR. RAINPROOF NEMA 3R ENCLOSURE, UL94V-0, UV RESISTANT. STAINLESS STEEL FASTENERS. STATIONARY L-BRACKET* IS COATED FOR OUTDOOR EXPOSURE, WET LOCATION. 5FT SJTOOW 14/3 PIGTAIL WITH LIGHTED MALE. 13 AMP RESETTABLE CIRCUIT BREAKER.

UPC 0-40082-43112-5	UL _{us} SJTOOW 14/3 30 ft	1625 WATT 13A 125V	YES	1	4	47.7lbs
---------------------	---------------------------------------	--------------------------	-----	---	---	---------

5320T-SW

INDOOR/OUTDOOR RETRACTABLE EXTENSION CORD REEL WITH 20 FT, SJTOOW 12/3 WIRE. WATERTIGHT NEMA 5-15C CONNECTOR. RAINPROOF NEMA 3R ENCLOSURE, UL94V-0, UV RESISTANT. STAINLESS STEEL FASTENERS. STATIONARY L-BRACKET* IS COATED FOR OUTDOOR EXPOSURE, WET LOCATION. 5FT SJTOOW 12/3 PIGTAIL WITH LIGHTED MALE. 15 AMP RESETTABLE CIRCUIT BREAKER.

UPC 0-40082-43111-8	UL _{us} SJTOOW 12/3 20 ft	1875 WATT 15A 125V	YES	1	4	48.5lbs
---------------------	---------------------------------------	--------------------------	-----	---	---	---------

5220T-D

INDOOR RETRACTABLE EXTENSION CORD REEL WITH 20 FT, SJTOOW 12/3 WIRE. DUAL DUPLEX PENDANT BOX. RUGGED SEALED ENCLOSURE. STAINLESS STEEL FASTENERS. POWDER COATED STATIONARY L-BRACKET*. 5FT SJTOOW 12/3 PIGTAIL WITH LIGHTED MALE. 15 AMP RESETTABLE CIRCUIT BREAKER.

UPC 0-40082-43114-9	UL _{us} SJTOOW 12/3 20 ft	1875 WATT 15A 125V	YES	4	4	52.8lbs
---------------------	---------------------------------------	--------------------------	-----	---	---	---------

*Additional Bracket Options Available



Incandescent Work Lights

Catalog No.
Description/UPC

Cord Type
Gauge/Length

Maximum
Rating

Master
Pack

Master
Cubic Feet

Master
Weight



HTL-25M-CB


HTL-50M-CB



Special Rotary hanging hook Rotates 360° and detents to hold light in place.


HTL-25M-CB

GROUNDING METAL REFLECTOR WITH OSHA WRAP AROUND 360° HEAVY DUTY METAL BULB / REFLECTOR GUARD WITH SPECIAL ROTARY HANGING HOOK. ON/OFF SWITCH, GROUNDING SIDE OUTLET WITH RESETTABLE 12 AMP CIRCUIT BREAKER BUILT INTO HANDLE. OUTDOOR ALL-WEATHER CORD REMAINS FLEXIBLE IN SUBZERO TEMPERATURES.

UPC 0-40082-00458-9  SJTW 14/3 1500 WATT 4[‡] 1.2 CU ft 17 lbs
25 ft 12A 125V


HTL-50M-CB

GROUNDING METAL REFLECTOR WITH OSHA WRAP AROUND 360° HEAVY DUTY METAL BULB / REFLECTOR GUARD WITH SPECIAL ROTARY HANGING HOOK. ON/OFF SWITCH, GROUNDING SIDE OUTLET WITH RESETTABLE 12 AMP CIRCUIT BREAKER BUILT INTO HANDLE. OUTDOOR ALL-WEATHER CORD REMAINS FLEXIBLE IN SUBZERO TEMPERATURES.

UPC 0-40082-00468-8  SJTW 14/3 1500 WATT 4 1.9 CU ft 25.1 lbs
50 ft 12A 125V

TLP-50GM-CB

GROUNDING SIDE OUTLET, RESETTABLE CIRCUIT BREAKER AND ON/OFF SWITCH BUILT INTO HANDLE. GROUNDING, COATED METAL BULB GUARD WITH SPECIAL ROTARY HANGING HOOK. OIL RESISTANT OUTDOOR ALL-WEATHER CORD REMAINS FLEXIBLE IN SUBZERO TEMPERATURES.

UPC 0-40082-00807-5  SJTOW 16/3 1500 WATT 6[‡] 2.1 CU ft 29 lbs
50 ft 12A 125V

[‡] Display tray pack

ABOVE UNITS HAVE A MAXIMUM OF 100 WATT LAMP RATING



TLP-50GM-CB



Fluorescent Work Lights

Catalog No.
Description/UPC

Cord Type
Gauge/Length

Maximum
Rating

Master
Pack

Master
Cubic Feet

Master
Weight




Grounded
Outlet
In Handle




UPL-25G

13 WATT PL LAMP, GROUNDING OUTLET, ON/OFF SWITCH BUILT INTO HANDLE, SWIVEL HANGING HOOK. 360° REMOVEABLE ROTATING MAGNET.

UPC 0-40082-00442-8  SJT 16/3 1440 WATT 4 .9 CU ft 15 lbs
25 ft 12A 120V

UPL-50G

13 WATT PL LAMP, GROUNDING OUTLET, ON/OFF SWITCH BUILT INTO HANDLE, ADJUSTABLE HANGING HOOK. 360° REMOVEABLE ROTATING MAGNET MOUNTING CLIP.

UPC 0-40082-00490-9  SJT 16/3 1440 WATT 4 .9 CU ft 22.2 lbs
50 ft 12A 120V



WHERE INNOVATION COMES TO LIGHT®



Incandescent Clamp Lamps




MCL6P

Catalog No. Description/UPC	Cord Type Gauge/Length	Maximum Rating	Master Pack	Master Cubic Feet	Master Weight
--------------------------------	---------------------------	-------------------	----------------	----------------------	------------------

MCL6P

4 IN 1 INCANDESCENT WORK LIGHT; STICK IT, CLAMP IT, HANG IT OR STAND IT. ALUMINUM REFLECTOR SHADE, MAGNETIC BASE, CLAMP, HANGING HOOK AND STAND BASE WITH REMOVABLE LEGS, 18/2 SPT2 CORD, 60 WATT MAX. BULB.

UPC 0-40082-00516-6	 SJTW 18/2 6 ft	60 WATT 120V	4	1 CU ft	8.25 lbs
---------------------	---	-----------------	---	---------	----------



Retractable Incandescent Work Light Reels




5000-50G-CB

Catalog No. Description/UPC	Cord Type Gauge/ Length	Maximum Rating	Circuit Breaker	No. of Outlets	Master Pack	Master Cubic Ft	Master Weight
--------------------------------	-------------------------------	-------------------	--------------------	-------------------	----------------	--------------------	------------------

5000-50G-CB

POWDER COATED STEEL REEL HOUSING. TROUBLE LIGHT WITH GROUNDED METAL BULB GUARD, ON/OFF SWITCH AND SIDE OUTLET BUILT INTO HANDLE WITH RESETTABLE CIRCUIT BREAKER.

UPC 0-40082-00446-6	 SJT 18/3 50 ft	875 WATT 7A 125V	YES	1	4	1.7 CU ft	37.8 lbs
---------------------	---	------------------------	-----	---	---	-----------	-------------



Retractable Data Reels



MCC2201

Catalog No. Description/UPC	Wire Type Length	Plug Type	Master Pack	Master Cubic Feet	Master Weight
--------------------------------	---------------------	-----------	----------------	----------------------	------------------

MCC2201

20FT RETRACTABLE CAT6 REEL. TANGLE FREE COMPACT CABLE STORAGE, RUGGED POWDER COATED REEL WITH 7.5"- 9" MOUNTING BRACKET. MOUNTS HORIZONTALLY OR VERTICALLY. HARDWARE AND INSTRUCTIONS INCLUDED.

UPC 0-40082-01253-9	CAT6 20 ft	Modular RJ46	4	.9 CU ft	13 lbs
---------------------	---------------	--------------	---	----------	--------



A  Pegasus Company

Merithian Products Corp.
9-300 Supertest Road
Toronto, Ontario, Canada
M3J 2M2

Phone: 905-669-0570
Toll Free: 800-920-8823
Fax: 905-669-1598
Email: sales@merithian.com
www.merithian.com

