

TRACERLINE®

PROFESSIONAL OEM GRADE LEAK DETECTION



HEAVY-DUTY & FLEET

FLUORESCENT LEAK DETECTION AND DIAGNOSTIC TOOLS



READY
FOR TOMORROW'S
CHALLENGES



TRUSTED BY
AUTOMOTIVE
LEADERS

— SINCE 1955 —



ISO 9001:2015 CERTIFIED COMPANY

TRACER PRODUCTS
A Division of Spectronics Corporation

ELECTRIC VEHICLE A/C DYE

oem
GRADE

BRIGHTER
DYE
PERFORMANCE

CO-SOLVENT
FREE



NEXT-GEN DYES

Electrically-driven A/C compressors require compatible leak detection dyes




TESTED EXTENSIVELY

Tracer Products manufactures electric and hybrid fluorescent dyes with OEM-grade A/C oil



COMPLETELY COMPATIBLE

Tracerline® electric dyes can be used in electrically driven automotive air conditioning systems without creating a safety issue



SCAN/CLICK FOR MORE INFO



POE-BASED EV A/C DYE UV LEAK DETECTION KIT

Compatible with both R-1234yf & R-134a

- ▶ EV A/C Leak Detection kit includes single-dose Mini-EZ™ dye cartridges, UV flashlight, solid-brass swivel-type R-134a coupler, R-1234yf adapter, GLO-AWAY™ Plus, and more.

TPOPUV20EV

- ▶ **TPOPUV** OPTI-PRO™ UV cordless, violet light LED leak detection flashlight
- ▶ **TP9815EV-P3*** (3) 0.25 oz (7 ml) Mini-EZ™ single-dose POE-Based EV A/C dye cartridges, services up to **3 vehicles**
- ▶ **TP9845** EZ-Ject™ dye injector assembly
- ▶ **TP-9813** Brass, swivel-type R-134a coupler with check valve and purge fitting for Mini-EZ™ capsules
- ▶ **TP9831** R-1234yf adapter
- ▶ **TP19** 2 oz (60 ml) spray bottle of GLO-AWAY™ Plus fluorescent dye cleaner

*Compatible with Hybrid Vehicles



NEW!

SERVICES
UP TO
3



UP TO 20ft (6m)
Inspection Range

3x AAA
Batteries Included



Fluorescence Enhancing



GLO-AWAY™ Plus +



Underhood Labels



R-1234yf Adapter



POE-BASED EV A/C DYE MINI-EZ™ INJECTION KIT

Compatible with both R-1234yf & R-134a

Product No.	Description
TP9815EV-P3*	(3) 0.25 oz (7 ml) Mini-EZ™ single-dose POE-Based EV A/C dye cartridges, services up to 3 vehicles
TP9815EV-P12*	(12) 0.25 oz (7 ml) Mini-EZ™ single-dose POE-Based EV A/C dye cartridges, services up to 12 vehicles
TP9814EV-BX*	<ul style="list-style-type: none"> ▶ TP9815EV-P3 (3) 0.25 oz (7 ml) Mini-EZ™ Single-Dose POE-Based EV A/C dye cartridges, services up to 3 vehicles ▶ TP9845 EZ-Ject™ dye injector assembly ▶ TP-9813 Solid-brass, swivel-type R-134a hybrid coupler with check valve and purge fitting ▶ TP9831 R-1234yf adapter

*Compatible with Hybrid Vehicles



NEW!

SERVICES
UP TO
3

AV electric vehicles
POE-BASED EV A/C OIL

NEW!



Compatible with both R-1234yf & R-134a

Product No.	Description
TP100EV-5*	5 oz (148 ml) foil pouch Viscosity: 84 cSt



*Compatible with Hybrid Vehicles

AV electric vehicles
POE-BASED EV A/C OIL + UV DYE

NEW!



Compatible with both R-1234yf & R-134a

Product No.	Description
TP100EVD-5*	5 oz (148 ml) foil pouch Viscosity: 84 cSt



*Compatible with Hybrid Vehicles

AV electric vehicles
PAG-BASED EV A/C DYE MINI-EZ™ INJECTION KIT

Compatible with both R-1234yf & R-134a

► Designed to meet manufacturer specifications for PAG compressors

Product No.	Description
TP9816EV-P3*	(3) 0.25 oz (7 ml) Mini-EZ™ single-dose PAG-Based EV A/C dye cartridges, services up to 3 vehicles
TP9816EV-P12*	(12) 0.25 oz (7 ml) Mini-EZ™ single-dose PAG-Based EV A/C dye cartridges, services up to 12 vehicles
TP9817EV-BX*	<ul style="list-style-type: none"> ► TP9816EV-P3 (3) 0.25 oz (7 ml) Mini-EZ™ single-dose PAG-Based EV A/C dye cartridges, services up to 3 vehicles ► TP9845 EZ-Ject™ dye injector assembly ► TP-9813 Solid-brass, swivel-type R-134a hybrid coupler with check valve and purge fitting ► TP9831 R-1234yf adapter



NEW!



*Compatible with Hybrid Vehicles



TO MEET INDUSTRY OEM SPECIFICATIONS



Compatible with R-134a & R-1234yf systems

Concentrated formula does not affect the system properties



Each cartridge is individually sealed to protect against moisture

DESIGNED WITH **DIELECTRIC PROPERTIES** TO **ENSURE SAFETY & COMPATIBILITY**



R-1234yf/PAG A/C DYE

oem
GRADE

BRIGHTER
DYE
PERFORMANCE

CO-SOLVENT
FREE

FLUORO-LITE® 5 BOTTLED DYE

A/C DYE FOR R-1234yf/PAG

For R-1234yf/PAG vehicle air conditioning systems. Use a Tracerline dye injector to add bottled dye into the A/C system.

MEETS **SAE**
J2297

BRIGHTER
DYE
PERFORMANCE



SERVICES
UP TO **32**

Product No.	Description
TP3825-8	8 oz (237 ml) R-1234yf/PAG bottle, services up to 32 vehicles
TP9883-BX	Inline Injector, 2 oz (60 ml) capacity. Control valve, R-1234yf hose/coupler & purge fitting.

See price list for all available dye sizes.

REFILLABLE INJECTOR

INLINE
INJECTOR



TP9883-BX



EZ-Ject™ SYSTEM

A/C DYE FOR R-1234yf/PAG


FEATURES:

- ▶ 0.5 oz (15 ml) cartridge
- ▶ Multi-dose, services up to **14 vehicles**

MEETS **SAE**
J2297

BRIGHTER
DYE
PERFORMANCE

Product No.	Description
TP9825-P3	(3) EZ-Ject™ R-1234yf/PAG cartridges
TP9824-BX	EZ-Ject™ Dye Injection Kit: <ul style="list-style-type: none"> ▶ TP9825 EZ-Ject™ R-1234yf/PAG cartridge ▶ TP9845 EZ-Ject™ dye injector assembly ▶ TP10 R-1234yf hose/coupler & purge fitting



TP9824-BX



EACH
SERVICES
UP TO **14**

BigEZ™ SYSTEM

A/C DYE FOR R-1234yf/PAG


FEATURES:

- ▶ 8 oz (237 ml) cartridge
- ▶ Multi-dose, services up to **64 vehicles**


MEETS **SAE**
J2297

BRIGHTER
DYE
PERFORMANCE

Product No.	Description
TP9725-8	8 oz (237 ml) BigEZ™ R-1234yf/PAG cartridge
TP9792-BX	EZ-Shot™ Dye Injection Kit: <ul style="list-style-type: none"> ▶ TP9725-8 BigEZ™ R-1234yf/PAG cartridge ▶ TP9749 EZ-Shot™ caulking gun-style dye injector assembly ▶ TP12 R-1234yf hose/coupler with BigEZ™ adapter & purge fitting



TP9792-BX



EACH
SERVICES
UP TO **64**

RECOMMENDED DYE DOSAGE:

	PRODUCT NUMBER	STANDARD DOSE
Fluoro-Lite® 5 Bottled Dye	TP3825	0.25 oz (7 ml)⓪ per 5 lbs (2 kg) of refrigerant or 10 oz (300 ml) of lubricant
EZ-Ject™ Cartridge	TP9825	0.035 oz (1 ml)⓪ per 2.5 lbs (1 kg) of refrigerant or 5 oz (150 ml) of lubricant
BigEZ™ Cartridge	TP9725	0.125 oz (3.7 ml)⓪ per 2.5 lbs (1 kg) of refrigerant or 5 oz (150 ml) of lubricant

⓪Equivalent to 1 line on bottle/cartridge



R-134a/PAG A/C DYE

FLUORO-LITE® 5 BOTTLED DYE

A/C DYE FOR R-134a/PAG


REFILLABLE INJECTOR

For R-134a/PAG vehicle air conditioning systems. Use a Tracerline dye injector to add bottled dye into the A/C system.



Product No.	Description
TP3820-8	8 oz (237 ml) R-134a/PAG bottle, services up to 32 vehicles
TP9882-BX	Inline Injector, 2 oz (60 ml) capacity. Control valve, R-134a hose/coupler & purge fitting.

See price list for all available dye sizes.



EZ-Ject™ SYSTEM

A/C DYE FOR R-134a/PAG



MULTI-DOSE

FEATURES:

- ▶ 0.5 oz (15 ml) cartridge
- ▶ Multi-dose, services up to **14 vehicles**



Product No.	Description
TP9860-P6	(6) EZ-Ject™ R-134a/PAG cartridges
TP9848-BX	EZ-Ject™ Dye Injection Kit: <ul style="list-style-type: none"> ▶ TP9860 EZ-Ject™ R-134a/PAG cartridge ▶ TP9845 EZ-Ject™ dye injector assembly ▶ TP9847 R-134a hose/coupler & purge fitting



BigEZ™ SYSTEM

A/C DYE FOR R-134a/PAG

HIGH-VOLUME DOSING

FEATURES:

- ▶ 8 oz (237 ml) cartridge
- ▶ Multi-dose, services up to **64 vehicles**



Product No.	Description
TP9760-8	8 oz (237 ml) BigEZ™ R-134a/PAG cartridge
TP9793-BX	EZ-Shot™ Dye Injection Kit: <ul style="list-style-type: none"> ▶ TP9760-8 BigEZ™ R-134a/PAG cartridge ▶ TP9749 EZ-Shot™ caulking gun-style dye injector assembly ▶ TP11 R-134a hose/coupler with BigEZ™ adapter & purge fitting



RECOMMENDED DYE DOSAGE:

	PRODUCT NUMBER	STANDARD DOSE
Fluoro-Lite® 5 Bottled Dye	TP3820	0.25 oz (7 ml)⓪ per 5 lbs (2 kg) of refrigerant or 10 oz (300 ml) of lubricant
EZ-Ject™ Cartridge	TP9860	0.035 oz (1 ml)⓪ per 2.5 lbs (1 kg) of refrigerant or 5 oz (150 ml) of lubricant
BigEZ™ Cartridge	TP9760	0.125 oz (3.7 ml)⓪ per 2.5 lbs (1 kg) of refrigerant or 5 oz (150 ml) of lubricant

⓪Equivalent to 1 line on bottle/cartridge

UNIVERSAL/ESTER A/C DYE



**CO-SOLVENT
FREE**

FLUORO-LITE® 5 BOTTLED DYE

A/C DYE FOR UNIVERSAL/ESTER

Tracerline® Universal/Ester dyes are designed to be compatible with all widely used refrigerants for automotive AC systems (R-1234yf, R-134a, and more).




SERVICES
UP TO
32

REFILLABLE INJECTOR

Product No.	Description
TP3840-8	8 oz (237 ml) Universal/Ester bottle, services up to 32 vehicles
TP9882-BX	Inline Injector, 2 oz (60 ml) capacity. Control valve, R-134a hose/coupler & purge fitting.

See price list for all available dye sizes.



EZ-Ject™ SYSTEM



A/C DYE FOR UNIVERSAL/ESTER

FEATURES:

- ▶ 0.5 oz (15 ml) cartridge
- ▶ Multi-dose, services up to **14 vehicles**



Product No.	Description
TP9870-P6	(6) EZ-Ject™ Universal/Ester cartridges
TP9841-BX	EZ-Ject™ Dye Injection Kit: <ul style="list-style-type: none"> ▶ TP9870 EZ-Ject™ Universal/Ester cartridges ▶ TP9845 EZ-Ject™ dye injector assembly ▶ TP9847 R-134a hose/coupler & purge fitting ▶ TP9831 R-1234yf adapter



BigEZ™ SYSTEM


A/C DYE FOR UNIVERSAL/ESTER

FEATURES:

- ▶ 8 oz (237 ml) cartridge
- ▶ Multi-dose, services up to **64 vehicles**



Product No.	Description
TP9770-8	8 oz (237 ml) BigEZ™ Universal/Ester cartridge
TP9790-BX	EZ-Shot™ Dye Injection Kit: <ul style="list-style-type: none"> ▶ TP9770-8 8 oz (237 ml) BigEZ™ Universal/Ester cartridge ▶ TP9749 EZ-Shot™ caulking gun-style dye injector assembly ▶ TP11 R-134a hose/coupler with BigEZ™ adapter & purge fitting ▶ TP9831 R-1234yf adapter



RECOMMENDED DYE DOSAGE:

	PRODUCT NUMBER	STANDARD DOSE
Fluoro-Lite® 5 Bottled Dye	TP3840	0.25 oz (7 ml)Ⓢ per 5 lbs (2 kg) of refrigerant or 10 oz (300 ml) of lubricant
EZ-Ject™ Cartridge	TP9870	0.035 oz (1 ml)Ⓢ per 2.5 lbs (1 kg) of refrigerant or 5 oz (150 ml) of lubricant
BigEZ™ Cartridge	TP9770	0.125 oz (3.7 ml)Ⓢ per 2.5 lbs (1 kg) of refrigerant or 5 oz (150 ml) of lubricant

NOTE: R-1234yf systems require TP9831 adapter

ⓈEquivalent to 1 line on bottle/cartridge

COOLANT DYES

WATER-BASED DYE

RITE-BLEND™ UNIVERSAL COOLANT DYE

For both Conventional & Extended-Life Coolants

OEM-Grade coolant dye that will not change the host color of the coolant. Works with all leak detection flashlights. Dye fluoresces yellow-green.


Product No.	Description
TP-3940-0008	8 oz (237 ml) bottle, services up to 8 vehicles

See price list for all available dye sizes.



RECOMMENDED DYE DOSAGE:

FLUID	TP-3940
Coolant	1 oz (30 ml) per 6 gal (23 L)



RETAINS THE ORIGINAL COOLANT COLOR

Compatible with **DEX-COOL®**

STANDARD COOLANT DYE

For all Conventional Coolants

Works with all leak detection flashlights. Dye fluoresces yellow-green.

Product No.	Description
TP-3900-0008	8 oz (237 ml) bottle, services up to 8 vehicles


NOTE: May alter the original color of the coolant
See price list for all available dye sizes.

Compatible with **DEX-COOL®**



RECOMMENDED DYE DOSAGE:

FLUID	TP-3900
Coolant	1 oz (30 ml) per 6 gal (23 L)



FLUID DYE FOR OIL-BASED SYSTEMS

oem
GRADE

BRIGHTER
DYE
PERFORMANCE

CO-SOLVENT
FREE

UV FLUORESCENT DYE

For all Circulating Oil-Based Fluid Systems

Patented, full-spectrum formulation. Works with all leak detection flashlights. Dye fluoresces yellow-green.

Product No.	Description
TP3400-8	8 oz (237 ml) bottle, services up to 8 vehicles

See price list for all available dye sizes.



RECOMMENDED DYE DOSAGE:

FLUID APPLICATIONS	
Engine Oil (includes Synthetics)	
Gasoline	1 oz (30 ml) per 4-6 qt (4-6 L)
Diesel	1 oz (30 ml) per 4 qt (4 L)
Power Steering	1 oz (30 ml) per 4 qt (4 L)
Automatic Transmission	1 oz (30 ml) per 6 qt (6 L)
Fuel (Gasoline + Diesel)	1 oz (30 ml) per 6-9 gal (23-34 L)
Hydraulics (Synthetic- or Petroleum-Based)	
Light-to-Medium Colored	1 oz (30 ml) per 2-3 gal (7.5-11 L)
Very Dark or Intensely Blue	1 oz (30 ml) per 2-3 qt (2-3 L)

UV FLUORESCENT DYE - MULTI-COLORED

For all Circulating Oil-Based Fluid Systems

With a set of color-coded leak detection dyes, a technician can diagnosis leaks across multiple, oil-based fluids – including transmission, oil and fuel. **Even in dirty diesel!**

Product No.	Description
TP3320-8	8 oz (237 ml) bottle, fluoresces white , services up to 8 vehicles
TP3340-8	8 oz (237 ml) bottle, fluoresces blue , services up to 8 vehicles
TP-3380-0008	8 oz (237 ml) bottle, fluoresces yellow , services up to 8 vehicles

See price list for all available dye sizes.



RECOMMENDED DYE DOSAGE:

FLUID APPLICATIONS	
Engine Oil (includes Synthetics)	
Gasoline	1 oz (30 ml) per 8-12 qt (8-12 L)
Diesel	1 oz (30 ml) per 8 qt (8 L)
Power Steering	1 oz (30 ml) per 8 qt (8 L)
Automatic Transmission	1 oz (30 ml) per 12 qt (12 L)
Fuel (Gasoline + Diesel)	1 oz (30 ml) per 12-18 gal (45-68 L)
Hydraulics (Synthetic- or Petroleum-Based)	
Light-to-Medium Colored	1 oz (30 ml) per 8 gal (30 L)
Very Dark or Intensely Blue	1 oz (30 ml) per 4 gal (15 L)

VIOLET LED FLASHLIGHTS | OPTI-PRO™ UV MAX R & UV MAX



OPTI-PRO™ UV MAX R
TPOPUVMR

The new OPTI-PRO™ UV MAX series offers the highest-quality leak detection lamps on the market.

With a more powerful beam profile, technicians can spot multiple leaks in A/C, coolant, and oil-based fluid systems.

LAMP SPECIFICATIONS

Run Time	5+ hours <i>(depending on power mode and usage)</i>
Charge Time	5 hours



35 ft (10.5 m) RANGE



USB RECHARGEABLE LI-ION BATTERY



POWERFUL BEAM



ADJUSTABLE FOCUS LENS



HIGH/LOW LIGHT



STROBE LIGHT



OPTI-PRO™ UV MAX
TPOPUVM

The TPOPUVM comes with all of the same great features as the TPOPUVMR – but it is instead powered by three AA batteries. Be confident all leak sites are found with this high-performance lamp.

The strobe light feature helps technicians contrast dye fluorescence from the surrounding area more easily. When there are multiple leaks present, this feature helps technicians pinpoint all leaks.

LAMP SPECIFICATIONS

Run Time	5+ hours <i>(depending on power mode and usage)</i>
-----------------	--



30 ft (9 m) RANGE



3 AA BATTERIES INCLUDED



POWERFUL BEAM



ADJUSTABLE FOCUS LENS



HIGH/LOW LIGHT



STROBE LIGHT



SCAN/CLICK FOR MORE INFO



SPOT POWER BEAM PROFILE
POWERFUL COVERAGE

MAX POWER



VIOLET LED FLASHLIGHTS | OPTI-PRO™ UV PLUS & UV

STROBE LIGHT:



The strobe feature helps technicians contrast the fluorescent effect even more! Makes leaks easier to spot throughout the entire system.

ADJUSTABLE FOCUS LENS:



2 in 1: Narrow focus for a powerful beam of light to fluoresce the smallest leaks. Wide focus for larger scans and to reduce reflections.



OPTI-PRO™ UV PLUS TPOUVP

LAMP SPECIFICATIONS

Run Time 5+ hours
(depending on power mode and usage)

Charge Time 5 hours

25 ft (7.5 m) RANGE

USB RECHARGEABLE LI-ION BATTERY

ADJUSTABLE FOCUS LENS

HIGH/LOW LIGHT

STROBE LIGHT



TP9940 – Fluorescence-enhancing glasses help to reduce glare and enhance leak detection results. Protect your eyes from glare, debris, and fluid.



OPTI-PRO™ UV TPOUV

LAMP SPECIFICATIONS

Run Time 4 hours

20 ft (6 m) RANGE

3 AAA BATTERIES INCLUDED

ADJUSTABLE FOCUS LENS



UV LED FLASHLIGHT

NEW!



LeakTracker™ MINI UV LED FLASHLIGHT TPLTM


FLUORESCES ALL DYES **UV LED** **25 FT (8 m) RANGE**

An advanced tool that illuminates all UV dyes, even within the dirtiest diesel engine oil. Its rugged IP68 rating ensures superior water and dust resistance.

LAMP SPECIFICATIONS

Light Source	UV LED
Range	Up to 25 ft (8 m)
Battery	3 AAA (included)
Run Time	6 hours (continuous)
Glasses	UV-absorbing

NOTE: TPLTM replaces TP-8695 (while supplies last)



In a single service call, a technician can scan all automotive fluid systems easily with the TPLTM ultraviolet leak detection flashlight.

LEAK DETECTION KITS

oem
GRADE

BRIGHTER
DYE
PERFORMANCE

CO-SOLVENT
FREE

UNIVERSAL/ESTER

COMPLETE SERVICE KIT

COMPLETE A/C + FLUID DYE UV LEAK DETECTION KIT

Compatible with R-1234yf, R-134a, and more **Oil-Based Fluids** **Coolant**

TPOPUV57HD

- ▶ **TPOPUV** OPTI-PRO™ UV cordless, violet light LED leak detection flashlight
- ▶ **TP9870 (2)** 0.5 oz (15 ml) cartridges of EZ-Ject™ Universal/Ester multi-dose A/C dye, services up to **14 vehicles each**
- ▶ **TP3400-8** 8 oz (237 ml) bottle of dye for all circulating oil-based fluids, services up to **8 vehicles**
- ▶ **TP-3900-0008** 8 oz (237 ml) bottle of Standard Coolant dye, services up to **8 vehicles**
- ▶ **TP9845** EZ-Ject™ dye injector assembly
- ▶ **TP9847** R-134a hose/coupler & purge fitting
- ▶ **TP19** 2 oz (60 ml) spray bottle of GLO-AWAY™ Plus fluorescent dye cleaner
- ▶ **TP9831** R-1234yf adapter



SERVICES
UP TO
28
A/C
SYSTEMS



UP TO
20 ft (6m)
Inspection
Range

3x
AAA
Batteries
Included



Fluorescence
Enhancing



GLO-AWAY™
Plus +



Underhood
Labels



R-1234yf
Adapter

**PINPOINT THE
EXACT SOURCE OF
MULTIPLE LEAKS IN
COLOR!**



OIL-BASED FLUID SYSTEMS

FLUID SERVICE KIT

MULTI-COLORED FLUID DYE UV LEAK DETECTION KIT

Oil-Based
Fluids

Coolant

Color-coded dyes for oil-based fluids: white dye, yellow dye, and blue dye. Green dye for treating coolant leaks.

TPLTM93HD

- ▶ **TPLTM** LeakTracker™ MINI UV LED cordless, leak detection flashlight
- ▶ **TP3320-8** 8 oz (237 ml) bottle of dye for all circulating oil-based fluids, fluoresces **white**, services up to **8 vehicles**
- ▶ **TP3340-8** 8 oz (237 ml) bottle of dye for all circulating oil-based fluids, fluoresces **blue**, services up to **8 vehicles**
- ▶ **TP-3380-0008** 8 oz (237 ml) bottle dye for all circulating oil-based fluids, fluoresces **yellow**, services up to **8 vehicles**
- ▶ **TP-3900-0008** 8 oz (237 ml) bottle of Standard Coolant dye, fluoresces **yellow-green**, services up to **8 vehicles**



SERVICES
UP TO
32
VEHICLE
SYSTEMS



UP TO
25 ft (8m)
Inspection
Range

3x
AAA
Batteries
Included



UV-absorbing
Glasses



Underhood
Labels



SCAN/CLICK FOR
MORE INFO

NOTE: TPLTM93HD replaces TPUV93HD (while supplies last)

Marksman™ II
ULTRASONIC DIAGNOSTIC TOOL
TP-9367L

SOUND SIGNATURE TECHNOLOGY 

Advanced heterodyne circuitry and “**sound signature technology**” to convert and amplify inaudible ultrasonic sounds into audible “**natural**” sounds.

Provides quick diagnosis of leaks and defects before they become major breakdowns!



SCAN/CLICK FOR MORE INFO

- ▶ 5-LED signal intensity indicator and audible alarm easily find exact problem source
- ▶ Self-adjusting Automatic Gain Control (AGC) circuitry enhances sensitivity and simplifies operation
- ▶ **Laser pointer** to help pinpoint the source of pressurized leaks
- ▶ Adjustable touch-control sensitivity pad and power switch

- ▶ Internal Noise Control (INC) ensures that tool is unaffected by ambient noise
- ▶ Checks for electrical discharge associated with insulation breakdown, carbon tracking and arcing
- ▶ Unique ultrasonic emitter helps locate faulty seals, gaskets and weather stripping in passenger cabs, trailers and other non-pressurized enclosures



APPLICATIONS:

- ▶ Automotive
- ▶ Heavy-duty trucks
- ▶ Air conditioning
- ▶ Refrigeration

IDEAL FOR DETECTING:

- ▶ Air brake leaks
- ▶ Compressed air leaks
- ▶ Vacuum leaks
- ▶ Tire leaks
- ▶ Gear and bearing wear
- ▶ Electrical discharge
- ▶ Exhaust leaks
- ▶ Refrigerant leaks



TRACER PRODUCTS

THE ONLY DYE INSTALLED ON THE ASSEMBLY LINE.



OEM

TRACERLINE®

THE ONLY UV DYE APPROVED BY OEM'S FOR USE ON THE ASSEMBLY LINE TO ENSURE QUALITY



OES & AFTERMARKET

HIGHEST-QUALITY LEAK DETECTION AND DIAGNOSTIC TOOLS

TRUSTED

BY MAJOR CAR MANUFACTURERS AND INSTALLED IN 300 MILLION VEHICLES



TRACER PRODUCTS A Division of Spectronics Corporation

265 Spagnoli Rd, #100, Melville, NY 11747 (800) 641.1133 | +1 516.333.1254

Orders@TracerProducts.com CustomerService@TracerProducts.com

www.TracerProducts.com



Scan/Click to learn more

